

element, wherein said pleated surface comprises pleats having an average pitch from about 0.0625 to about 5 inches, said second filter element being configured to selectively remove a second contaminant from a liquid when contacted therewith, wherein said second filter element contains a laminate having two or more layers of filter media.

5. (Amended) A multi-component liquid filter as defined in claim 1, wherein said pleats have an average pitch from about 0.125 to about 1 inch.

6. (Amended) A multi-component liquid filter as defined in claim 1, wherein said pleats are disposed longitudinally in a direction transverse to fluid flow through said second filter element.

8. (Amended) A multi-component liquid filter as defined in claim 7, wherein said first and said second filter elements are generally cylindrical, said generally cylindrical filter elements being arranged in fluid communication within said chamber coaxial with respect to a longitudinal centerline of said chamber.

12. (Amended) A multi-component liquid filter as defined in claim 1, wherein at least one of said filter elements comprises a material selected from the group consisting of microfiber glass, a charge-modified material, a nonwoven web, a bed of granular material, a cellulosic material, activated carbon, airlaid composites, and combinations thereof.

13. (Amended) A multi-component liquid filter as defined in claim 1, wherein said laminate has a layer containing activated carbon laminated to at least one other layer containing a nonwoven web.

23. (Amended) A multi-component liquid filter device, comprising:
a chamber;

a first generally cylindrical filter element, and a second generally cylindrical filter element, said filter elements arranged in fluid communication within said chamber coaxial with respect to a longitudinal centerline of said chamber;

one of said first and second filter elements having inner and outer circumferential surfaces defined by a generally constant radius therearound so as to define generally continuous planar circumferential filtering surfaces for a liquid passing radially through said filter element;

AS cont
the other of said respective filter elements having inner and outer circumferential surfaces defined by surface contours such that said circumferential surfaces have a non-constant radius therearound so as to define a generally discontinuous non-planar circumferential filtering surface with a greater effective filtering surface area compared to a continuous planar filtering surface for a liquid passing radially through said other filter element, wherein said filter element having surface contours contains a laminate having two or more layers of filter media; and

wherein liquid flows radially through said filter elements within said chamber such that different contaminants are removed by said respective filter elements prior to the liquid flowing from said chamber.

Li 102 ✓
AG
31. (Amended) A filter device as defined in claim 23, wherein at least one of said filter elements comprises a material selected from the group consisting of microfiber glass, a charge-modified material, a nonwoven web, a bed of granular material, a cellulosic material, activated carbon, airlaid composites, and combinations thereof.

Li + 3rd
32. (Amended) A filter device as defined in claim 23, wherein said laminate has a layer containing activated carbon laminated to at least one other layer containing a nonwoven web.